

NEW – Meet the AirLink® XR60, the World’s Smallest Rugged 5G Router – Now with 5-Year Warranty, **Learn more →**
Support and Management. Limited-Time Offer!

AirLink® LX40

Ultra Compact 4G Router

The AirLink® LX40 is a compact LTE router offering “out-of-the box” LTE and Wi-Fi connectivity that is simple to install. The LX40 supports security, digital signage and IoT applications in fixed, protected environments.



- PoE – Power Over Ethernet
- IP21 Rated
- AirLink Complete
- 4G Cat-4
- Single 1x1 Wi-Fi 5
- 1x Ethernet (1 Gbps)



AirLink® LX40 – Router Specifications

| | North America | EMEA | Australia & New Zealand |
|-----------------|--------------------------------|--------------------------------|--------------------------------|
| CELLULAR | | | |
| Peak D/L | Up to 150 Mbps, Cat-4 (WP7610) | Up to 150 Mbps, Cat-4 (WP7607) | Up to 150 Mbps, Cat-4 (WP7609) |
| Peak U/L | Up to 50 Mbps | Up to 50 Mbps | Up to 50 Mbps |

4G LTE

| | | | |
|------------------------|-------------------------------------|--------------------------|-------------------------|
| Frequency Bands | B1, B4, B5, B12, B13, B14, B17, B66 | B1, B3, B7, B8, B20, B28 | B1, B3, B5, B7, B8, B28 |
|------------------------|-------------------------------------|--------------------------|-------------------------|

3G WCDMA/HSPA+

| | | | |
|------------------------|------------|--------|------------|
| Frequency Bands | B2, B4, B5 | B1, B8 | B1, B5, B8 |
|------------------------|------------|--------|------------|

2G GSM/GPRS

| | |
|------------------------|-----------|
| Frequency Bands | 900, 1800 |
|------------------------|-----------|

Approvals

| | | | |
|-------------------|----------------|---------|----------|
| Regulatory | FCC, IC, PTCRB | GCF, CE | GCF, RCM |
|-------------------|----------------|---------|----------|

| | |
|----------------|-------------------------|
| Carrier | AT&T, Verizon, T-Mobile |
|----------------|-------------------------|

Part Numbers

| | | | |
|---------------------|-------------------------|--------------------------|--------------------------|
| Part Numbers | 1104579, 1104573 (WiFi) | 1104181, 1104182 (Wi-Fi) | 1104183, 1104184 (Wi-Fi) |
|---------------------|-------------------------|--------------------------|--------------------------|

HOST INTERFACES

1 Gigabit RJ-45 Ethernet Port (POE)
 USB 2.0 Micro-B Connector
 2 SMA antenna connectors (cellular, diversity)
 1 RP SMA antenna connector (Wi-Fi)

SECURITY

Remote Authentication (LDAP, RADIUS, TACACS+) DMZ
 Inbound and Outbound Port filtering
 Inbound and Outbound Trusted IP
 MAC Address Filtering
 PCI compatible
 Secure Firmware Update

WI-FI (OPTIONAL)

Dual Band 2.4/5GHz Wi-Fi
 802.11 b/g/n/ac (Wave2 Client Mode)
 Support for 10 clients, WPA2 Enterprise
 Output power 16dBm per channel
 Access Point or Client Mode (Wi-Fi as WAN)
 Single SSID Support
 Captive Portal

LAN (ETHERNET/USB)

DHCP Server
 IP Passthrough
 VLAN
 Host Interface Watchdog
 PPPoE

ENVIRONMENTAL

Operating Temperature -20°C to +65°C / -4°F to +149°F (+60°C / +140°F when using PoE)

Storage Temperature -40°C to +85°C / -40°F to +185°F

Humidity 90% RH @ 60°C

Military Spec MIL-STD-810G conformance to shock, vibration, thermal shock, and humidity
 IP21 rated ingress protection

POWER

Input/Operating Voltage 7 to 36 VDC

Power Modes Low voltage disconnect to prevent battery drain
 Built-in protection against voltage transients
 Power-over-Ethernet (PoE) powered device
 Ignition Sense with time delay shutdown

INPUT/OUTPUT

Configurable I/O pin on power connector
Digital Inputs: ON Voltage: 2.7 to 36 VDC
Configurable Pull-ups for dry contact input
Digital Open Collector Output > sinking 500 mA
Analog Inputs: 0.5-36VDC (range selectable)

NETWORK AND ROUTING

Network Address Translation (NAT) Reliable Static Route
Port Forwarding Dynamic DNS
Policy Routing Verizon PNTM
NEMO/DMNR IPV6 Gateway
VRRP

VPN

IPsec, GRE, and OpenVPN Client
Up to 5 concurrent tunnels
Split Tunnel
Dead Peer Detection (DPD)

ROUTER MANAGEMENT INTERFACES

Local web user interface
AT Command Line Interface (Telnet/SSH)
SNMP
SMS Commands

APPLICATION FRAMEWORK

ALEOS Application Framework (AAF)
LUA Scripting Language

EVENTS ENGINE

Custom event triggers and reports
Configurable interface, no programming

Event Types

Digital Input, Network Parameters, Data Usage, Timer, Power, Device Temperature and Voltage

Report Types

RAP, SMS, Email, SNMP Trap, TCP (Binary, XML, CSV)

Event Actions

Drive Relay Output

INDUSTRY CERTIFICATIONS

Safety

IECEE Certification Bodies Scheme (CB Scheme), UL 60950

Vehicle Usage

E-Mark (UN ECE Regulation 10.04), ISO7637-2, SAE J1455 (Shock, Vibration, Electrical)

Environments

RoHS2, REACH, WEEE

Public Safety

FirstNet®

SUPPORT AND WARRANTY

1 year standard warranty with up to 5 years extended warranty with current AirLink Complete subscription. Unrestricted critical firmware updates.

ACCESSORIES

In The Box

LX40, DC Power Cable and Quick Start Guide

Other Accessories (sold separately)

2000579 AC Adapter, 12VDC
6001221 DIN Rail Bracket
6001110 Cellular Paddle Antenna
6001111 Wi-Fi 2.4/5Hz Paddle Antenna


For antenna options visit: sierrawireless.com/antennas

CONSTRUCTION

Polycarbonate housings that meet MIL-810/IP21 environmental standards.

DIMENSIONS

103 mm (111 mm including connectors) x 79 mm x 25 mm
4.1 in (4.4 in including connectors) x 3.1 in x 1.0 in
Weight: 250g



**For carrier specific band support please refer to the hardware user guide.*